

SafetyPro™ Plus 9G

DETAILED PRINTER SPECIFICATIONS



11918 SE Division St. #109
Portland OR 97266
Toll Free: (877) 762-9280
Fax: (503) 761-2838
www.industrialsafetysolution.com



Software Specifications

Bundled Software	Labeling Suite Arc Flash RTK Database Windows Drivers
Bundled Images	900+ OSHA, ANSI and general safety pictograms in WMF (vector) format
Supported Barcodes	Linear 2D 3D 30+ Symbologies
Programmable	TSPL-EZ

Print Specifications

Print Resolution	300 DPI
Print Speed	2" – 4"/sec
Media Width	4" – 8"
Media Length	150'

Physical Specifications

Physical Dimensions	17.32" x 13.23" x 19.84" (W x H x D)
Max. Material Size	8.2" OD
Weight	51 lbs (Unloaded)

System Specifications

Computer Interface	USB 2.0 Parallel (Centronics) Serial (RS-232) Ethernet Server
Processor	32-bit High Performance
Memory	8MB Flash 32MB SDRAM SD Expansion (to 4G)

Service Specifications

Power	100V-120V @ 60Hz 220-240V @ 50Hz
Storage Temperature	-40F - 140F
Service Temperature	41F - 104F

**The SafetyPro conforms to the following International Safety Specifications:
FCC Class A, CE Class A, UL, CUL, TUV**

The SafetyPro Plus 9G Industrial Labeling System is an industrial-grade label and sign printer. This unit was engineered for durability and long print life. Under heavy use, the print-head components should last at least 1 million inches. Industrial Safety Solutions offers certified repair, reconditioning and replacement services should your label printer need attention.

Toll Free Tech Support: (877) 762-9280 - www.industrialsafetysolution.com

Copyright 2009, Industrial Safety Solutions - Document Version 2.00