

SafetyPro™ Label Printer

DETAILED PRINTER SPECIFICATIONS



11918 SE Division St. #109
Portland OR 97266
Toll Free: (877) 762-9280
Fax: (503) 761-2838
www.industrialsafetysolution.com



Software Specifications

Bundled Software	LabelView XLT+ Easy Label Creator RTK Label Creator Windows Drivers
-------------------------	--

Bundled Images	900+ OSHA, ANSI and general safety pictograms in WMF (vector) format
-----------------------	---

Supported Barcodes	Linear 2D 3D 30+ BC Lang.
---------------------------	------------------------------------

Programmable	TSPL2 TPLE BASIC
---------------------	------------------------

Print Specifications

Print Quality	High-Def 128µm
Print Speed	Up to 5"/sec
Media Width	0.5" – 4.25"
Media Length	150' (1800")

Physical Specifications

Physical Dimensions	12.36" x 8.39" x 7.40" (L x W x H)
Max. Material Size	5" OD
Weight	6.5 lbs (Unloaded)

System Specifications

Computer Interface	USB Parallel Serial Ethernet (opt.)
---------------------------	--

Processor	32-bit RISC CPU
Memory	2MB Flash 2MB DRAM 8MB (opt.)

Service Specifications

Power	AC Input: 100V-240V Universal Switching DC Output: 24V @ 3.75A
Storage Temperature	-40F - 140F
Service Temperature	41F - 104F

The SafetyPro conforms to the following International Safety Specifications:
FCC Class B | CE Class B | C-Tick | BSMI | CCC | UL | CUL / TUV/GS

The SafetyPro Industrial Labeling System is an industrial-grade desktop class label and sign printer. This unit was engineered for durability and long print life. Under heavy use, the print-head components should last at least 1 million inches. Industrial Safety Solutions offers certified repair, reconditioning and replacement services should your label printer need attention.

Toll Free Tech Support: (877) 762-9280 - www.industrialsafetysolution.com

Copyright 2007, Industrial Safety Solutions - Document Version 2.01