

SafetyPro™ Label Printer

DETAILED PRINTER SPECIFICATIONS



11918 SE Division St. #109
Portland OR 97266
Toll Free: (877) 762-9280
Fax: (503) 761-2838
www.industrialsafety.com



Software Specifications

Bundled Software	FacilityWare Label Manager RTK Label Creator Arc Flash Label Creator Windows Drivers
Bundled Images	2500+ OSHA, ANSI and general safety pictograms in WMF (vector) format
Supported Barcodes	Code 39 Over 30 additional (opt.)
Programmable	TSPL2 TPLE BASIC

Print Specifications

Print Quality	High-Def 300DPI
Print Speed	Up to 7"/sec
Media Width	0.5" – 4.25"
Media Length	150' (1800")

Physical Specifications

Physical Dimensions	12.36" x 8.39" x 7.40" (L x W x H)
Max. Material Size	5" OD
Weight	6.5 lbs (Unloaded)

System Specifications

Computer Interface	USB 2.0 Parallel Serial Ethernet (opt.)
Processor	32-bit RISC CPU
Memory	4MB Flash 8MB SDRAM SD Expansion

Service Specifications

Power	AC Input: 100V-240V Universal Switching DC Output: 24V @ 3.75A
Storage Temperature	-40F - 140F
Service Temperature	41F - 104F

The SafetyPro conforms to the following International Safety Specifications:
FCC Class B | CE Class B | C-Tick | BSMI | CCC | UL | CUL / TUV/GS

The SafetyPro Industrial Labeling System is an industrial-grade desktop class label and sign printer. This unit was engineered for durability and long print life. Under heavy use, the print-head components should last at least 1 million inches. Industrial Safety Solutions offers certified repair, reconditioning and replacement services should your label printer need attention.

Toll Free Tech Support: (877) 762-9280 - www.industrialsafety.com

Copyright 2011, Industrial Safety Solutions - Document Version 4.00