

SafetyPro™

DETAILED PRINTER SPECIFICATIONS



SOFTWARE SPECIFICATIONS

Bundled Software	FacilityWare Label Manager RTK Label Creator Arc Flash Label Creator Windows Drivers
Bundled Images	2500+ OSHA, ANSI and general safety pictograms in WMF (vector) format
Supported Barcodes	Code 39 Over 30 additional (opt.)
Programmable	TSPL2 TPLE BASIC

PRINT SPECIFICATIONS

Print Resolution	300 DPI
Print Speed	Up to 7"/sec
Media Width	0.5" – 4.25"
Media Length	150' (1800")

PHYSICAL SPECIFICATIONS

Physical Dimensions	12.36" x 8.39" x 7.40" (L x W x H)
Max. Material Size	5" OD
Weight	6.5 lbs (Unloaded)

SYSTEM SPECIFICATIONS

Computer Interface	USB 2.0 Parallel Serial Ethernet (opt.)
Processor	32-bit RISC CPU
Memory	4MB Flash 8MB SDRAM SD Expansion

SERVICE SPECIFICATIONS

Power	AC Input: 100V-240V Universal Switching DC Output: 24V @ 3.75A
Storage Temperature	-40F - 140F
Service Temperature	41F - 104F

The SafetyPro conforms to the following International Safety Specifications: FCC Class B | CE Class B | C-Tick | BSMI | CCC | UL | CUL / TUV/GS

The SafetyPro Industrial Labeling System is an industrial-grade desktop class label and sign printer. This unit was engineered for durability and long print life. Under heavy use, the printhead components should last at least 1 million inches. Industrial Safety Solutions offers certified repair, reconditioning and replacement services should your label printer need attention.

 **CALL US TODAY FOR MORE INFORMATION**
Toll Free: **1-877-762-9280**